

Online Oxygen Monitor with Alarms & Battery Backup



The OMD-351-O2 Ambient Air Monitor is designed to measure and assure the appropriate levels of both oxygen in an enclosed or confined area. Personnel safety is a primary issue in nearly every industry and is magnified within confined spaces where oxygen depletion or asphyxiation due to a leak in an inert gas container can quickly and unexpectedly take place.

The OMD-351-O2 is designed with an easy to use interface with features that are optimized for safety and mitigate the dangers of confined spaces and oxygen deficiency. The analyzer comes with 2 pre-configured oxygen concentration alarms that match the OSHA recommendations of 19.5% and 20.0%. Alarm functionality comes in the form of 2 fully adjustable, form C non-latching, relay contacts, an integral audible buzzer and local LED's loaded into the front of the unit. The unit also has a built in POWER FAIL relay contact.

The unit comes standard with an integral battery backup which helps accentuate "brown out" conditions. With this standard feature, power outages will not interfere with a properly working monitor. The standby power source uses a rechargeable lead acid battery.

The oxygen sensor used in the OMD-351-O2 is based on the galvanic electrochemical fuel cell principal. The sensors are self-contained and minimal maintenance is required - no need to clean electrodes or add electrolyte.

0 - 30% O2 Concentration Range

Optional CO2 Integration (OMD-351-O2-CO2)

0 - 10,000 PPM CO2 Concentration Range

Two Concentration Relay Contact Alarms

Power Failure Alarm Relay Contact

Integral Audible Buzzer Alarm

Integrated Rechargeable Battery Backup

Integral Visual Alarm LEDs

Specifications

Accuracy:	< +/- 1% of Full Scale Range*
Calibration:	Periodically
Alarms:	(2) Adjustable Relay Contacts (1) Power Fail Relay Contact
Audible Alarm:	Integral
Visual Alarms:	Panel Mounted LED's
Analyzer Range:	0 - 30% O2
Output:	4 - 20mA (1 each O2 / CO2)
Battery Backup:	Rechargeable
Power:	100 - 240 VAC
Display:	Large with Backlight
Dimensions:	9.5x 6.5 x 3.8 inch
Enclosure:	Anodized Aluminum
Weight:	4.6 lbs
Temperature:	0 to 50° C
Temperature Compensation:	Integral
Sensor:	PO2-AMB, CO2-AMB
Sensor Life:	60 Months (Approximately)
Response Time:	T90 in 10 Seconds
Sensor Warranty:	12 months
Analyzer Warranty:	12 months

*Accuracy at constant conditions

Optional Configurations:

24V DC Input Power

Remote Oxygen Sensor (OMD-351-O2-Remote)

O2 / CO2 Dual Ambient Air Monitor (OMD-351-O2-CO2)